





# SR52UT INTIMIDATOR

Extended-range rechargeable LED flashlight

| MAX   | TOTAL   | THROW   |
|---|---|---|
|  |  |  |
| 1100<br>lumens  | 40<br>h   | 800<br>m  |



Cree XP-L HI LED inside

# SR52UT INTIMIDATOR

Extended-range rechargeable LED flashlight



## MARKET APPLICATIONS

searching, rescue, law enforcement, and the outdoors.

SR52UT UPC: 692654091819

MSRP: \$119.95

## DESCRIPTION

The SR52 ULTRA THROWER INTIMIDATOR (SR52UT) is developed from the previous SR52 platform. The SR52UT features the latest Cree XP-L HI LED that has a maximum output of 1100 lumens and reaches a maximum beam distance of 800 meters. The SR52-UT is an ideal solution for searching & rescue, law enforcement, and the outdoors.



Cree XP-L HI LED

# SR52UT INTIMIDATOR

Extended-range rechargeable LED flashlight



## FEATURES

- Features a Cree XP-L HI LED, maximum output of 1100 lumens, and a beam distance of 800m.
- Three brightness levels plus a strobe mode: 1100 lumens, 550 lumens, 80 lumens, and a 10Hz strobe mode
- 99% light transmittance rate through the tempered glass lens that features a two-sided anti-reflective coating
- Built-in charging circuit for the 18650 rechargeable lithium ion batteries through a built-in micro USB charging port on the body of flashlight
- Heat sink body design allows more efficient heat dissipation
- Features three parallel battery compartments including reverse polarity protection to prevent improper battery installation
- Powered by an 18650 battery featuring a protection board with a bulged battery positive end
- Wide input voltage range from 3 ~ 9 volts compatible with CR123A batteries but cannot be charged with them
- flat tail cap providing the ability to place it upside down
- Lanyard hole on the end of the tail cap
- Anti-scratch type III hard anodizing aluminum body

## OUTPUT

| FL1 STANDARD | MODE 1      | MODE 2     | MODE 3    |
|--------------|-------------|------------|-----------|
|              | 1100 lumens | 550 lumens | 80 lumens |
|              | 4 h         | 7.5 h      | 40 h      |
|              | 800 m       |            |           |
|              | 160,000 cd  |            |           |

Strobe mode: 10Hz

## LENS

Tough ultra-clear tempered glass with anti-reflective coating

## LIGHT SOURCE

1 x Cree XP-L HI CW LED

## DIMENSIONS

**Length:** 6.3 in / 161.5 mm

**Bezel Diameter:** 2.48 in / 63mm

**Weight:** 14.3 oz / 405 g (excluding batteries)

## BODY MATERIAL

type-III hard anodized aluminum

## BATTERY SOURCE

3 x 18650

## WARRANTY

Olight's 5 Year warranty.

Visit [olightworld.com/warranty](http://olightworld.com/warranty)

## ACCESSORIES

- Micro-USB Cable
- 18650 x3(optional)
- Holster
- USB Vehicle Power Adapter
- Spare O-rings x 2
- User Manual

**WATERPROOF**  
IPX 8



**DROP TEST**



**COMPLIANCE**



[olightworld.com](http://olightworld.com)

All performance claims to ANSI/NEMA FL1-2009 Standard. Made in China.

© Olight 7/29/15 V1